

# **DATA SHEET**



## Retractable Universal Mount 4K HDMI® Adapter Ring with Colour Coded Mini DisplayPort<sup>™</sup>, DisplayPort, and USB-C<sup>®</sup>

Attach a Retractable Universal Mount with colour coded adapters to an HDMI cable to provide connectivity options for a meeting space display

#### **OVERVIEW**

The Patent Pending Retractable Universal Mount 4K HDMI Adapter Ring is the perfect addition to conference rooms, huddle spaces, lecture halls or classrooms to make sure that anyone can connect. The standard configuration includes the adapters to connect nearly any device to the in-room display, while supporting up to a 4K video resolution. Standard configuration includes HDMI to DisplayPort, Mini DisplayPort, or USB-C adapters to meet connectivity challenges.

Colour Coded Adapters: Each adapter is colour coded with a band that saves time and frustration by making it easy to quickly identify the adapter you need.

Integrated Pull Tab: Easily grab the adapters when you need them with the integrated Pull Tab that is also available to be customised to feature your company or organisation logo. Minimum order quantities apply to customised Pull Tabs.

Retractable Universal Mount: The Retractable Universal Mount attaches to any flat surface, like a table or lectern, providing mounting flexibility to best fit your environment. The retractor extends out to 4.9ft, ensuring that the adapters are always within reach when needed, and the retractor is tested to over 20,000 extension cycles for a long service life.

Tools Included: To simplify the process, installation tools for mounting the adapters and optional stopper are included.

#### **FEATURES**

- Adapters support up to a 4K video resolution, so meeting attendees will be able to see the displayed content for improved comprehension and detailed decision making.
- Adapters are colour coded, so no more frustration trying to find the adapter that you typically use for your laptop.
- Integrated pull tab, so the adapters can be accessed quickly or easily reached when they are tucked away.
- Installation tools are included, so you save time and money by not needing to purchase any additional tools.

#### **ITEM DESCRIPTION**

84269 Retractable Universal Mount 4K HDMI Adapter Ring with Colour Coded Mini DisplayPort, DisplayPort, and USB-C



# DATA SHEET

## **SPECIFICATIONS:**

## Retractable Universal Mount 4K HDMI Adapter Ring with Colour Coded Mini DisplayPort, DisplayPort, and USB-C

#### SIGNAL SPECIFICATIONS:

- USB Type-C to HDMI Adapter: 100% Functional Test at 4K/60Hz/4:4:4 Resolution with Standard AV Test Equipment
- DisplayPort to HDMI Adapter: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment
- Mini DisplayPort to HDMI Adapter: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment

### **ELECTRICAL SPECIFICATIONS:**

- USB Type-C to HDMI Adapter Power Consumption: 1050mW (210mA/5.0V)
- DisplayPort to HDMI Adapter Power Consumption: 396mW (120mA/3.3V)
- Mini DisplayPort to HDMI Adapter Power Consumption: 396mW (120mA/3.3V)

### **PHYSICAL SPECIFICATIONS:**

- Operating Temperature: 0°C 40°C (0% 90%RH)
- Storage Temperature: -10°C 60°C (0% 90%RH)

### **PHYSICAL CHARACTERISTICS:**

- HDMI 19pin Female Connector: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- USB Type-C Male Connector: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- DisplayPort Male Connector: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP Black, Shell: Nickel Plated
- Mini DisplayPort Male Connector: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP Black, Shell: Nickel Plated
- Adapter Hood: Molded Black (Pantone/#Black 6C) PVC
- USB Type-C to HDMI Adapter Colour Band: Green (Pantone#354C) 12 x 1.5mm
- DisplayPort to HDMI Adapter Colour Band: Red (Pantone#032C) 12 x 1.5mm
- Mini DisplayPort to HDMI Adapter Colour Band: Yellow (Pantone#012C) 12 x 1.5mm
- Retractor 093: 63.5 x 63.5 x 17.5mm, Black Steel Wire OD: 1.2mm, ABS Shell with Hex Nut Tool and Black Locking Coupler (x2)
- Black Metal Screws (x4): 6.8 x 22mm, M3, Material: Steel
- Black Metal Screws (x4): 6.5 x 22.5mm, M3.5, Material: Steel
- Pull Tab: 80 x 25 x 2mm, Material: Polyester, Black Background, White Text, with Black Eyelet
- Universal Mounting Bracket: 85 x 65 x 1.2mm, Material: C.R.S., Rigidity: 1/4H (HV110-120/HRB 40-45), Colour: Black
- Product is CE marked and conforms to 2011/65/EU ROHS 2





# **DATA SHEET**

C2G HDMI

43.75 (1.722″)

C2G

HDMI

Ρ1

28.00 (1.102″)

R1.2

DISPLAY

ø

12.00 (0.472") USB-C

SOURCE

P

11.15 (0.439″)

Ρ3 

### **SPECIFICATIONS:**

Retractable Universal Mount 4K HDMI Adapter Ring with Colour Coded Mini DisplayPort, DisplayPort, and USB-C





Great King Street North Birmingham, West Midlands B19 2LF UK Phone (0)800 328 2916 EMEA Phone +44 (0)1952 677300 www.c2g.com/uk



